

Schäkel - hochfest, geschweißt mit überstehendem Bolzen

WLL kg	Ng	Maße gemäß Zeichnung (mm)							Gewicht kg
		b1	b2	b3	d1	d3	d4	h1	
500	1/4"	12	15	19	6	17	8	28	7
750	5/16"	13	29	21	8	21	10	31	10
1.000	3/8"	16	36	26	10	26	12	36	18
1.500	7/16"	18	40	29	11	28	14	42	25
2.000	1/2"	21	47	33	13	30	16	48	37
3.250	5/6"	27	59	43	16	42	20	60	71
4.750	3/4"	32	70	51	19	48	22	71	127
6.500	7/8"	36	80	58	22	57	27	84	178
8.500	1"	43	93	68	25	62	30	95	252
9.500	1 1/8"	46	104	74	29	69	33	109	353
12.000	1 1/4"	52	115	82	32	78	36	119	504
13.500	1 3/8"	57	127	92	35	86	39	133	684
17.000	1 1/2"	60	136	98	38	94	42	146	878
25.000	1 3/4"	73	161	127	44	112	52	178	1.409
35.000	2"	83	185	146	51	127	55	197	2.090
55.000	2 1/2"	105	232	184	64	152	70	267	3.990
85.000	3"	127	279	200	76	200	82	330	6.200
120.000	3 1/2"	137	321	232	92	220	95	374	10.900
150.000	4"	145	353	250	104	240	108	372	13.000

Ng = Nenngröße / WLL = Tragfähigkeit (ca. kg)

